



Tel. +41 44 860 2233
Fax: +41 44 860 2616
GSM: +41 79 403 5555

Security Printing Consulting AG

Büelrebenstr. 10, CH-8185 Winkel/ZH, **Switzerland**
e-mail: info@spc-ag.ch web: www.spc-ag.ch

ML1200

Stand Alone Passport Laminator





Passport Laminator ML1200

Compact size desk top laminator to process open passport booklets for thin resin laminates or conventional laminates.

Closed passport booklets are manually inserted into the pre-heated laminator. The ML1200 transports automatically the passport booklet through the roll laminator where the laminate is pressed from two sides and firmly applies the laminated by heated roll at the pre-set corresponding laminating temperature.

The ML1200 is a high quality laminator and is for one by one lamination in decentralized passport issuing sites or in Embassies.

Advantages are: short lamination times, compact and maintenance free, low noise operation with minimum power consumption.

Technical data

Dimensions		
Dimensions	L x W x H	340 x 260 x 115 mm
Gross weight		Approx. 6,5 kg
Foundation/flooring		
Temperature	Operation	10 °C - 35 °C
	Storage	- 20 °C - +55 °C
Ambient conditions		
Relative humidity	Operation	at +25 °C - 80 % RH (not condensed)
	Storage	at +25 °C - 90 % RH (not condensed)
Working Parameters		
Laminating	Temperature stepless	110 °C - 220 °C
	Temperature tolerance	± 0.5°C
	Working speed	30 to 40 Seconds per booklet or 500 mm – 900 mm/min
	Temperature tolerance	± 0.5°C
	Start up time	< 2 Minutes
Thickness	Max. document thickness	6 mm
	Factory adjustable to customer requirements	
Other Conditions		
EMC Air purity	In conformity with the CE-standard	
Electricity		
	Voltage	110 V or 240 V
	Frequency	50 Hz – 60 Hz
	Rated current	1 A
	Power consumption	ca. 900 W